

COOLING DUTY

- Air on to heat exchanger at 25°C (cooled water off at 35°C)
- Ambient temperature range for the standard design
- Cooled water temperature (in the standard design)

Note: equipment subject to ambients below 5°C will require antifreeze or mechanical frost protection system.

Kcal/hr	5160
kW	6
°C	+10°C to +50°C
°C	Ambient +10°C

COOLING SYSTEM

- Heat exchanger - Air cooled
- Surface area
- Rejection capacity
- Fan arrangement
- diameter
- speed
- air flow
- motor power
- Material

No. off	One
m ²	0.27
Kcal/hr	5160
No. off	One
mm	457
rpm	1370
m ³ /hr	3060
kW	0.18
	Copper tube / aluminium fin

WATER SYSTEM

- Water system instruments - See options list
- Bulk holding tank - Capacity
- Water glycol filling point
- Overflow
- Water pump - Type
- Flow
- Pressure
- Motor power
- Material
- Pipework - Material
- Connections - Warm water INLET
- Cooled water OUTLET

litres	8
male BSP	½" or manual filling
male BSP	½"
	Centrifugal
m ³ /hr	0.5
bar	3.0
kW	0.37
	Bronze
	Copper/nylon
male BSP	¾"
male BSP	¾"

ELECTRICAL SYSTEM

- Mains supply for the standard design
- Control supply
- Total nominal power
- Protection rating
- Full load under normal operation
- Electrical controls: direct on line. Incorporates safety overload.

Volt phase cycle	415-3-50
Volt phase cycle	N/A
kW	0.55
	IP44
Amp	1.8

NOISE LEVEL (freefield)

dB'A' @ 3m	67
------------	----

DRY WEIGHT

kg	91
----	----

DIMENSIONS (mm)

Width	692
Depth	692
Height	675

- Finish: Light Admiralty Grey BS381C 697

OPTIONS

- | | | |
|------------------------------------|--------------------------------------|-------------------------------|
| Temperature gauge | High pressure pump | Low water flow |
| Pressure gauge | Special control systems | High pressure pumps |
| Pressure relief valve | Frost protection | Twin pumps |
| Flow switch | Weatherproofing | Stainless steel tank |
| Pressure switch | Materials of construction | Remote control |
| Fan thermostat | Remote control | Special electrical circuits |
| Over temperature stat | Copper/copper heat exchanger | 24V control circuit |
| Tank liquid level visual indicator | Systems suitable for deionised water | Finish, colour of your choice |
| Level switch | High water flow | |